

Technical data sheet

Bolt tie FAZ II P A5

Item number: 3498996



Bolt tie FAZ II Plus for the anchoring of medium to heavy loads in cracked or uncracked concrete. Suitable for high loads with small edge and axial distances. For knocking in.

European Technical Assessment ETA-99/0520, including characteristic values under fire exposure to fire resistance R 120.

Proof of suitability in the event of seismic impacts, categories C1 and C2.




A5 Stainless steel

Master data

Item number	3498996
Type	FAZIIPlus12/10A5
Description 1	Bolt anchor
Manufacturer	OBO
Dimension	M12x110
Colour	stainless steel
Material	Stainless steel
Smallest sales unit	20
Unit of quantity	Piece
Weight	9.63 kg
Weight unit	kg/100 pc.

Dimensions



Length	104 mm
Dimension L	104 mm

Technical data sheet

Bolt tie FAZ II P A5

Item number: 3498996



Technical data

Version for	For pushing in
Anchor/nail/bolt version	Spreading anchor
Drill hole depth	88.5 mm
Drill hole diameter, min.	12 mm
Thread	M12
Thread metric	12
Thread type	Metric
Thread length	59 mm
Clamping strength	10 mm
WAF	19
Approvals available	yes
Mounting type, anchor, tie	Push-through mounting Pre-mounting Stand-off mounting
Tie screw system	Hexagon head
Clamping range, max.	25 mm
Clamping range, min.	10 mm
ETA earthquake rating	C1 and C2