Technical data sheet T piece 60/300 A4

Item number: 6038184



T piece for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.






A4 Stainless steel 2B Bright, treated

Master data

Item number6038184Description 1T pieceDescription 2for cable tray, horizontalManufacturerOBODimension60x300Colourstainless steelMaterialStainless steelSurfaceBright, treatedSurface standard1Unit of quantityPieceWeister0414 Ler		
Description 2for cable tray, horizontalManufacturerOBODimension60x300Colourstainless steelMaterialStainless steelSurfaceBright, treatedSurface standard1Unit of quantityPiece	Item number	6038184
ManufacturerOBODimension60x300Colourstainless steelMaterialStainless steelSurfaceBright, treatedSurface standard1Unit of quantityPiece	Description 1	T piece
Dimension 60x300 Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard 1 Unit of quantity Piece	Description 2	for cable tray, horizontal
Colour stainless steel Material Stainless steel Surface Bright, treated Surface standard 1 Unit of quantity Piece	Manufacturer	OBO
Material Stainless steel Surface Bright, treated Surface standard 1 Unit of quantity Piece	Dimension	60x300
Surface Bright, treated Surface standard Bright, treated Smallest sales unit 1 Unit of quantity Piece	Colour	stainless steel
Surface standard I Smallest sales unit 1 Unit of quantity Piece	Material	Stainless steel
Smallest sales unit 1 Unit of quantity Piece	Surface	Bright, treated
Unit of quantity Piece	Surface standard	
	Smallest sales unit	1
Weight 044 Abr	Unit of quantity	Piece
vveight 211.4 kg	Weight	211.4 kg
Weight unit kg/100 pc.	Weight unit	kg/100 pc.

Item number: 6038184





Width	300 mm
Height	60 mm
Plate thickness	1 mm
Dimension B	300 mm

Technical data

Connector version	Integrated connector
Maintain electrical functions	yes
NATO hole pattern	no
Rustproof steel, pickled	no
Permitted temperature range, max.	120 °C
Permitted temperature range, min.	-20 °C
Wide-span version	no
Type of connector, cable support system	Screwed
Recommended quantity of bolts	21 St.
Rail thickness	1.25 mm