

Technical data sheet

Cable gland, EX area, metric thread, black

Item number: 2050374



Cable gland with EU design type approval certificate for products and protection systems for use in accordance with the regulations in explosion-hazard area. Directive 2014/34/EU.

EU design type approval certificate number: BKI23ATEX0030 X.

With metric connecting thread to IEC 423.

Sealing ring of chloroprene/nitrile rubber, moulded sealing, so no connection thread sealing ring needed.

Protection IP 68 at 3 bar.



PA Polyamide

Master data

Item number	2050374
Type	VTEC EX M50 SW
Description 1	Cable gland, EX area
Manufacturer	OBO
Dimension	M50
Colour	Black
Material	Polyamide
Smallest sales unit	5
Unit of quantity	Piece
Weight	9.2 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	0,4032 kg CO2e / 1 Piece


Technical data sheet

Cable gland, EX area, metric thread, black

Item number: 2050374



Dimensions



Dimension E	68.5 mm
Dimension G	M50 mm
Dimension L max.	57 mm
Dimension L min.	42 mm
Dimension L1	13 mm
Dimension L2	9 mm

Technical data

Type of seal	Sealing ring
Version for	Straight
Bend protection	no
Sealing area D, max.	38 mm
Sealing area D, min.	32 mm
explosion-proof	yes
Flat cable gland	no
For Ex zone	yes
For Ex zone gas	1, 2
For Ex zone dust	21, 22
Thread	M50 x 1,5
Thread type	Metric
Thread length	13 mm
Nominal thread size	50
Thread increase	1.5 mm
Fibre-glass reinforced	no
Halogen-free	yes
Unstable torque	17 Nm
Sealing insert, multiple	no
With locknut	no
ROHS-conformant	yes
Impact-resistant	no
WAF	60
Protection rating	IP68
Hexagonal corner dimension	68.5 mm
Splittable gland	no
Permitted temperature range, max.	65 °C
Permitted temperature range, min.	-20 °C
Strain relief option	no